

## 5.5 Peak HP 20 Gallon Air Compressor

### Product Features:

- 2 cylinder cast iron single stage oil lubricated pump
- 150 PSI Max pressure for optimum tool performance
- ASME registered tank
- ASME safety valve
- Wisconsin Electric 5.5 peak HP motor with reset
- Belt drive with sturdy metal belt guard
- Large intake "Auto-drop" filters
- Air pressure regulator and easy to read pressure gauges
- Pump with "V" style design minimizes vibrations, improves cooling and extends compressor life
- 10" pneumatic wheels and a front handle for portability



<b>MODEL</b>	<b>KC-2051H2</b>
<b>MOTOR (PEAK)</b>	5.5 HP
<b>FACTORY PRESSURE SETTING (ADJUSTABLE UP TO)</b>	95-125 PSI (150 PSI)
<b>AIR DELIVERY @ 40 PSI</b>	7.6 CFM
<b>AIR DELIVERY @ 90 PSI</b>	6.0 CFM
<b>TANK SIZE</b>	20 Gallon
<b>MOTOR AMPERAGE</b>	15/7.5 Amp.
<b>RPM</b>	3,450
<b>VOLTAGE</b>	120V/240V, 1 Phase, 60 Hz
<b>PRE-WIRED</b>	120V
<b>ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT</b>	39-1/2" x 20-1/2" x 31" / 145 lbs
<b>PACKAGE DIMENSIONS (LxWxH) / WEIGHT</b>	35-3/4" x 19-1/2" x 31" / 155 lbs
<b>UPC</b>	7 72995 01094 3