



5.4 Peak HP Air Compressor

Product Features:

- 2 cylinder cast iron single stage oil lubricated pump
- 150 PSI Max pressure for optimum tool performance
- ASME registered tank
- ASME safety valve
- Wisconsin Electric 5.5 peak HP motor with reset
- Belt drive with sturdy metal belt guard
- Large intake "Auto-drop" filters
- Air pressure regulator and easy to read pressure gauges
- Pump with "V" style design minimizes vibrations, improves cooling and extends compressor life
- 10" pneumatic wheels and a front handle for portability



MODEL	KC-3124V2
MOTOR (PEAK)	5.5 HP
FACTORY PRESSURE SETTING (ADJUSTABLE UP TO)	95-125 PSI (150 PSI)
AIR DELIVERY @ 40 PSI	7.6 CFM
AIR DELIVERY @ 90 PSI	6.0 CFM
TANK SIZE	24 Gallon
MOTOR AMPERAGE	15 / 7.5 Amp.
RPM	3,450
VOLTAGE	120V / 240V, 1 Phase, 60 Hz
PRE-WIRED	120V
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	24-1/2" x 21-1/4" x 47" / 160 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	29" x 20-1/4" x 50" / 170 lbs
UPC	7 72995 01216 9

Specifications subject to change.